

Lappas

climbing.com

LOWER - OFF
GAIA Ti
200150 / 250150 / 300150

Lower-Off Gaia Ti - Titanium Gr2
Σταθμός Ασφάλισης Lower-Off Gaia Ti - Τιτάνιο

technical sheet / τεχνικό φυλλάδιο

suitable for
κατάλληλο για



*Li (Installation length) = at least twice (2) the length of the Body of the rock anchor

resistance requirements
statics tests
απαιτήσεις στατικής φόρτισης

A	EN 959:2018	15kN
	UIAA 123	20kN
B	EN 959:2018	25kN
	UIAA 123	25kN

effective strength / μέγιστη φόρτιση

A 22,6kN **B** 27,4kN **C** 58kN

C orient the anchor towards the direction of the load

installation / τοποθέτηση

* Db = Diameter body
Dh = Diameter hole

APPROVED USE / ΟΡΘΗ ΧΡΗΣΗ

WARNING / ΠΡΟΣΟΧΗ
RISK OF ACCIDENT / ΚΙΝΔΥΝΟΣ ΑΤΥΧΗΜΑΤΟΣ

After the resin, do not touch the anchor and use it placed no earlier than 24 hours, even better if not least after 2/3 days (dependent on ambient temperature...).

Still comply with the direction set by the factory of the resin used.

The use of polyester type glue shall not be recommended.

rock / βράχος rope / σκοινί